

DETAILED SPECIFICATION SHEET

Optimum Flow Olive



Yarn Type	UV Polyethylene - W Shape
Denier	10800 / 4400
Approximate Pile Height	1.5 in.
Machine Gauge	3/8 inch
Roll Size	15 x 100 linear feet
Approximate Infill Amount	1.0 lb / psf
Primary Backing	Optimum Flow™
Total Product Weight	83.66 oz/yd²
Face Weight	49.20 oz/yd²
Average Tuft Bind Strength	10.8 lbs/force
Total Lead Content	<0.5 mg/Kg
Pill Flammability	8 out of 8 Pass
Water Permeability	331.3 inches/hour
QUV Accelerated Weathering	Color: 9 / Texture: 10

Recommended Uses

- Landscape
- Commercial
- Play Areas
- Pets

Equipped with Optimum Flow™ technology for exceptional drainage. Optmum Flow Olive is our preferred product for pet applications due to its permeability and slightly stiffer blade structure, which makes cleaning a breeze. Also perfect for landscape, putting fringe, and anywhere else a medium density product is needed.h




16 Year Warranty



Optimum Flow™ Technology



Made in the U.S.A.





DETAILED SPECIFICATION SHEET

Optimum Flow Forest



Yarn Type	UV Polyethylene - W Shape
Denier	10800/4400
Approximate Pile Height	1.5 in.
Machine Gauge	3/8 inch
Roll Size	15 x 100 linear feet
Approximate Infill Amount	1.0 lb / psf
Primary Backing	Optimum Flow™
Total Product Weight	83.66 oz/yd²
Face Weight	49.20 oz/yd²
Average Tuft Bind Strength	10.8 lbs/force
Total Lead Content	<0.5 mg/Kg
Pill Flammability	8 out of 8 Pass
Water Permeability	331.3 inches/hour
QUV Accelerated Weathering	Color: 9 / Texture: 10

Recommended Uses

- · Landscape
- Commercial
- Play Areas
- Pets

Equipped with Optimum Flow™ technology for exceptional drainage. Optimum Flow Forest is our preferred product for pet applications due to its permeability and slightly stiffer blade structure, which makes cleaning a breeze. Also perfect for landscape, putting fringe, and anywhere else a medium density product is needed.



16 Year Warranty



Optimum Flow™ Technology



Made in the U.S.A.

